




# CCFL Specifications

## Key Features

- Sunlight Readable
- 16:9 Wide
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Fast Response Time
- Thin and Light
- 12 CCFL



## ALF/ALH2225 (CMO M220Z1-L02)

| Model No.                | ALF2225                                          | ALH2225                                                     |
|--------------------------|--------------------------------------------------|-------------------------------------------------------------|
| LCD Display              | 22" Wide TFT LCD Module                          | 22" Wide TFT LCD Module                                     |
| Display Area             | 473.76 x 296.1mm                                 | 473.76 x 296.1mm                                            |
| Brightness               | 1000 cd/m <sup>2</sup>                           | 1000 cd/m <sup>2</sup>                                      |
| Resolution               | 1680x1050 (WSXGA <sup>+</sup> )                  | 1680x1050 (WSXGA <sup>+</sup> )                             |
| Contrast Ratio           | 700 : 1                                          | 700 : 1                                                     |
| Pixel Pitch (mm)         | 0.282(H) x 0.282(V)                              | 0.282(H) x 0.282(V)                                         |
| Viewing Angle            | +85°~-85°(H), +80°~-80°(V)                       | +85°~-85°(H), +80°~-80°(V)                                  |
| Display Colors           | 16.7M colors                                     | 16.7M colors                                                |
| Response Time            | 5ms (Typical)                                    | 5ms (Typical)                                               |
| Sync                     | LVDS                                             | LVDS                                                        |
| Power Consumption        | 65W                                              | 70W                                                         |
| Inverter                 | LI 1222A                                         | LI 1222A                                                    |
| Control Board (Optional) |                                                  | AD5621GA (Standard)                                         |
| F / R Control Button     |                                                  | Power Switch, Menu, Select (+,-), Auto                      |
| OSD Menu                 |                                                  | Brightness, Contrast, H/V Position, Color, Phase, Clock.... |
| Dimensions (WxHxD)       | 493.7x320.1x26.8mm                               | 493.7x320.1x26.8mm                                          |
| Weight                   | 2630g                                            | 2730g                                                       |
| Optional                 | <input checked="" type="checkbox"/> Touch Screen |                                                             |

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

|                                                |                                                   |
|------------------------------------------------|---------------------------------------------------|
| <b>Control Board (Optional)</b>                | AD5766GDVA/AD1501GDV                              |
| <input checked="" type="checkbox"/> AD5766GDVA | VGA+CVBS+S-Video+Audio (Optional DVI / Component) |
| <input checked="" type="checkbox"/> AD1501GDV  | VGA+DVI+S-Video                                   |
| <b>F / R Control Button</b>                    | 5 Key / 4 Key (Optional)                          |
| <input checked="" type="checkbox"/> 5 Key      | Power Switch, Menu, Select (+,-), Auto            |
| <input checked="" type="checkbox"/> 4 Key      | Power Switch, Menu, Select (+,-)                  |

ALF= Panel+Inverter

ALH= Panel+Inverter+Control Board





Note :

- 1.Outline Tolerance : 0.5mm
- 2.Lamp Connector : JST BHR-03VS-1
- 3.Lamp Cable : U13239 AWG22 L=150±5mm



*Enrich your visual world....*