

AOT Specifications



Key Features

- Sunlight Readable
- LED Backlight
- -20°C~60°C Wide Temp.
- Low Power Consumption
- High Shock & Vibration Resistance
- 90% High Uniformity
- Low EMI Noise
- Wide Dimming
- Multiple Mounting Choices
- 70000hrs Life Expectancy



OLF/OLH0615 (PVIPD064VT4)

Model No.	OLF0615	OLH0615
LCD Display	6.4" LED Backlight	6.4" LED Backlight
Display Area	129.6 x 97.4 mm	129.6 x 97.4 mm
Brightness	1000 cd/m ²	1000 cd/m ²
Resolution	640 x 480 (VGA)	640 x 480 (VGA)
Contrast Ratio	400 : 1	400 : 1
Pixel Pitch (mm)	0.2025(H) x 0.203(V)	0.2025(H) x 0.203(V)
Viewing Angle	120°(H), 95°(V)	120°(H), 95°(V)
Display Colors	262K colors	262K colors
Response Time	40ms	40ms (Typical)
Sync	TTL	TTL
Power Consumption	11W	16W
LED Driving Board	LI D06A	LI D06A
Control Board (Optional)		AD5621GA (Standard)
F / R Control Button		Power Switch, Menu, Select (+,-), Auto
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	178.8x126.8x20.4mm	178.8x126.8x20.4mm
Weight	340g	440g
Optional	☒ Touch Screen	

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA
☒ AD5621GA	VGA+Audio
☒ AD5621GD	VGA+DVI
☒ AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
F / R Control Button	5 Key / 4 Key (Optional)
☒ 5 Key	Power Switch, Menu, Select (+,-), Auto
☒ 4 Key	Power Switch, Menu, Select (+,-)

OLF= Panel+Driving Board+AOT

OLH= Panel+Driving Board+Control Board+AOT

