

AOT Specifications



Key Features

- Sunlight Readable
- LVDS
- Long Lamp Life
- Thin and Light
- 8 CCFL



OLF/OLH1226 (TOSHIBA LTD121EC5S)

Model No.	OLF1226	OLH1226
LCD Display	12.1" TFT LCD Module	12.1" TFT LCD Module
Display Area	245.76 x 184.32mm	245.76 x 184.32mm
Brightness	1250 cd/m ²	1250 cd/m ²
Resolution	1024x768 (XGA)	1024x768 (XGA)
Contrast Ratio	250 : 1	250 : 1
Pixel Pitch (mm)	0.24(H) x 0.24(V)	0.24(H) x 0.24(V)
Viewing Angle	+70°~-70°(H), +55°~-70°(V)	+70°~-70°(H), +55°~-70°(V)
Display Colors	262K colors	262K colors
Response Time	50ms (Max)	50ms (Max)
Sync	LVDS	LVDS
Power Consumption	32W	37W
Inverter	LI 0812A	LI 0812A
Control Board (Optional)		AD5621GA (Standard)
F / R Control Button		Power Switch, Menu, Select (+,-), Auto
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	292.9x220x27.58mm	292.9x220x27.58mm
Weight	1115g	1215g
Optional	☒ Touch Screen	

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA
☒ AD5621GA	VGA+Audio
☒ AD5621GD	VGA+DVI
☒ AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
F / R Control Button	5 Key / 4 Key (Optional)
☒ 5 Key	Power Switch, Menu, Select (+,-), Auto
☒ 4 Key	Power Switch, Menu, Select (+,-)

OLF= Panel+Inverter+ AOT

OLH= Panel+Inverter +Control Board+AOT

