

AOT Specifications



Key Features

- Sunlight Readable
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Fast Response Time
- Thin and Light
- 12 CCFL

New



OLF/OLH1550 (CMO G150X1-L02)

Model No.	OLF1550	OLH1550
LCD Display	15" TFT LCD Module	15" TFT LCD Module
Display Area	304.128 x 228.096 mm	304.128 x 228.096 mm
Brightness	2200 cd/m ²	2200 cd/m ²
Resolution	1024x768 (XGA)	1024x768 (XGA)
Contrast Ratio	700 : 1	700 : 1
Pixel Pitch (mm)	0.297(H) x 0.297(V)	0.297(H) x 0.297(V)
Viewing Angle	+80°~-80°(H), +80°~-80°(V)	+80°~-80°(H), +80°~-80°(V)
Display Colors	16.2M colors	16.2M colors
Response Time	25ms (Typical)	25ms (Typical)
Sync	LVDS	LVDS
Power Consumption	42W	47W
Inverter	LI 1215A	LI 1215A
Control Board (Optional)		AD5621GA (Standard)
F / R Control Button		Power Switch, Menu, Select (+,-), Auto
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	326.5x253.5x21.5mm	326.5x253.5x21.5mm
Weight	2070g	2070g
Optional	☒ Touch Screen	

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.



Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
☒ AD5621GA	VGA+Audio
☒ AD5621GD	VGA+DVI
☒ AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
☒ AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
☒ 5 Key	Power Switch, Menu, Select (+,-), Auto
☒ 4 Key	Power Switch, Menu, Select (+,-)

OLF= Panel+Inverter+ AOT

OLH= Panel+Inverter +Control Board+AOT