



## NAVPIXEL™ NPD1954

### 19" IP65 Sunlight Readable Marine Display

NAVPIXEL™ NPD1954, the high-performance, rugged touch monitor, is specially engineered to survive from the most demanding working environment. Housed in a milled billet aluminum case, the slim-profile NAVPIXEL™ NPD1954 is light weight and watertight with fully sealed IP65 connectors. The front-mounted sunlight readable touchscreen makes the industrial rugged monitor vividly and user-friendly. In addition, the high power efficiency and low heat design guarantee the stability and longevity required for mission critical deployment.

#### Main Features

- 1000 Nits Sunlight Readable LCD
- Long Life, Low Power Consumption LED Backlight
- -10°C~50°C Wide Operation Temperature
- Advanced Optical Bonding (AOT)
- Resistive Touch Support
- IP65 Waterproof
- 8~36V DC input

#### Application:

- Marine

Specifications are subject to change without notice.  
All brands or product names are trademarks or registered trademarks of their respective companies.

## Specifications

### LCD Display

#### Backlight

- 19" LED Backlight

#### Active Display Area

- 376.32x301.06 mm

#### Brightness

- 1000 cd/m<sup>2</sup>

#### Resolution

- 1280x1024 (SXGA)

#### Contrast Ratio

- 900:1

#### Pixel Pitch (mm)

- 0.294(H)x0.294(V)

#### Viewing Angle

- 160°(H), 160°(V)

#### Display Color

- 16.2M

#### Response Time

- Tr 3.6ms/ Tf 1.4ms

#### Inputs

- VGAX2, DVIx2, Composite x3, RS232x1

#### Picture in Picture

- 3 stages (child, split and wide screen)

### Mechanical

#### IP Rating

- Fascial waterproof to IP65 standards when console mounted.

#### Construction

- Rugged Aluminum Alloy Chassis

#### Mounting

- Panel (Flush) mount, VESA mount

#### Dimension

- 421.9mm (W) x 304.1mm(H) x 56mm(D)

#### Net Weight

- To be advised

### Power

#### Voltage

- Operates on 12V and 24V systems

#### Power Consumption

- 40~45W

### Environmental

#### Operating Temperature

- -10°C~50°C (14°F~122°F)

#### Non-Operating Temperature


- -20°C~70°C (-4°F~158°F)

### Certification


- Designed to meet FCC Class A  
DNV Marine Approval Pending

## Outline Dimensions


Unit: mm



## Control Button



## Connectors



## Ordering Information

NPD1954-ETAW-H01

## Optional Accessories

**840612111200** Power Adapter 12V, 10A, 120W, PAC120F

**810618301010** Power cord (US type)

**810618301090** Power cord (European type)