

Platform Specifications



Key Features

- 22" Sunlight Readable
- 16:9 Wide, WXGA
- Available Input: VGA, DVI, AVx2
S-video, Component
- 5Wx2 Speakers
- Split Windows
- Content Update Remotely
(If Optional Server & Client Management
Software Purchased)
- Power Input: 110V-240v AC
- Media Player Build in: HMP-500S



SLA2225 (CMO M220Z1-L02)

Model No.	SLA2225
LCD Display	22" Wide TFT LCD Module
Display Area	473.76 x 296.1mm
Brightness	1000 cd/m ²
Resolution	1680x1050 (WSXGA ⁺)
Contrast Ratio	700 : 1
Pixel Pitch (mm)	0.282(H) x 0.282(V)
Viewing Angle	+85°~-85°(H), +80°~-80°(V)
Display Colors	16.7M colors
Response Time	5ms (Typical)
Sync	LVDS
Power Consumption	70W
Inverter	LI 1222A
Control Board (Optional)	AD5621GA (Standard)
F / R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	545x370x61.6mm
Weight	6.61kgs
Optional	☒ Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5766GDVA/AD1501GDV
☒ AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
☒ AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
☒ 5 Key	Power Switch, Menu, Select (+,-), Auto
☒ 4 Key	Power Switch, Menu, Select (+,-)

SLO= Open Frame

SLD= Industrial Casing

