

Platform Specifications



Key Features

- w/2wx2 speakers
- Aluminum stand (optional)
- 5-wire resistive touch screen (optional)
- Foldable stand , angle, height adjustment
- Security lock hole
- 75mm VESA mounting



SLM1931 (AUO M190EG02)

Model No.	SLM1931
LCD Display	19" TFT LCD Module
Display Area	376.32 x 301.056 mm
Brightness	300 cd/m ²
Resolution	1280x1024 (SXGA)
Contrast Ratio	800 : 1
Pixel Pitch (mm)	0.294(H) x 0.294(V)
Viewing Angle	+80°~-80°(H), +80°~-80°(V)
Display Colors	16.7M colors
Response Time	5ms (Typical)
Sync	LVDS
Power Consumption	59W
Inverter	LI 0419A
Control Board (Optional)	AD5621GA (Standard)
F / R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	485x435x173mm
Weight	4.1kgs (N/W) / 7Kgs (G/W)
Optional	☒ Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
☒ AD5621GA	VGA+Audio
☒ AD5621GD	VGA+DVI
☒ AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
☒ AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
☒ 5 Key	Power Switch, Menu, Select (+,-), Auto
☒ 4 Key	Power Switch, Menu, Select (+,-)

SLM= Monitor

