

Platform Specifications



Key Features

- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Fast Response Time
- Thin and Light



SLO1541 (AUO M150XN07 V9)

Model No.	SLO1541
LCD Display	15" TFT LCD Module
Display Area	304.128 x 228.096 mm
Brightness	250 cd/m ²
Resolution	1024x768 (XGA)
Contrast Ratio	700 : 1
Pixel Pitch (mm)	0.297(H) x 0.297(V)
Viewing Angle	+70°~-70°(H), +65°~-60°(V)
Display Colors	16.2M colors
Response Time	8ms (Typical)
Sync	LVDS
Power Consumption	28W
Inverter	LI 0215A
Control Board (Optional)	AD5621GA (Standard)
F / R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	402x314x46.3mm
Weight	3.42kgs
Optional	☒ AOT ☒ Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
☒ AD5621GA	VGA+Audio
☒ AD5621GD	VGA+DVI
☒ AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
☒ AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
☒ 5 Key	Power Switch, Menu, Select (+,-), Auto
☒ 4 Key	Power Switch, Menu, Select (+,-)

SLO= Open Frame

SLD= Industrial Casing



A photograph of a museum platform. Three monitors are mounted on the wall, displaying various images. Below them, a person is leaning over a display case filled with small, framed photographs or documents. The word "Platform" is written in large, bold, black letters at the bottom of the image.

Outline Dimensions
unit:mm



Note: 1. 4 different AD boards can be selectable.
2. Temper glass and touch screen can be installed.

██████████