

Platform Specifications



Platform

Key Features

- Sunlight Readable
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Fast Response Time
- Thin and Light
- 12 CCFL



SLD1756 (CPT CLAA170EA07)

Model No.	SLD1756
LCD Display	17" TFT LCD Module
Display Area	337.92 x 270.336 mm
Brightness	1200 cd/m ²
Resolution	1280x1024 (SXGA)
Contrast Ratio	700 : 1
Pixel Pitch (mm)	0.264(H) x 0.264(V)
Viewing Angle	+80°~-80°(H), +80°~-80°(V)
Display Colors	16.2M colors
Response Time	5ms (Typical)
Sync	LVDS
Power Consumption	70W
Inverter	LI 1217A
Control Board (Optional)	AD5621GA (Standard)
F / R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	436x373x61.6mm
Weight	6.33kgs
Optional	☒ Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
☒ AD5621GA	VGA+Audio
☒ AD5621GD	VGA+DVI
☒ AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
☒ AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
☒ 5 Key	Power Switch, Menu, Select (+,-), Auto
☒ 4 Key	Power Switch, Menu, Select (+,-)

SLO= Open Frame

SLD= Industrial Casing



A photograph of a museum platform. Three monitors are mounted on the wall, displaying various images. Below them is a long display case containing numerous small, framed photographs or documents. A person is visible in the background, looking at the display.

Outline Dimensions
unit:mm



Note:1.OSD membrane can be on front or rear cover.
2.4 different AD boards can be selectable.
3.Light sensor and VR are optional function.
4.Temper glass and touch screen can be installed.
