

Platform Specifications



Platform

Key Features

- Sunlight Readable
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Thin and Light
- 12 CCFL



SLD1946 (AUO M190EG01)

Model No.	SLD1946
LCD Display	19" TFT Active Matrix Panel
Display Area	376.32 x 301.056 mm
Brightness	700 cd/m ²
Resolution	1280x1024 (SXGA)
Contrast Ratio	1300 : 1
Pixel Pitch (mm)	0.294(H) x 0.294(V)
Viewing Angle	+89°~-89°(H), +89°~-89°(V)
Display Colors	16.7M colors
Response Time	20ms (Typical)
Sync	LVDS
Power Consumption	59W
Inverter	LI 1219A
Control Board (Optional)	AD5621GA (Standard)
F / R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	451x343.1x58mm
Weight	5.35kgs
Optional	☒ Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
☒ AD5621GA	VGA+Audio
☒ AD5621GD	VGA+DVI
☒ AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
☒ AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
☒ 5 Key	Power Switch, Menu, Select (+,-), Auto
☒ 4 Key	Power Switch, Menu, Select (+,-)

SLO= Open Frame

SLD= Industrial Casing



A photograph of a museum platform. Three monitors are mounted on the wall, displaying various images. Below them is a long display case containing numerous small, framed photographs or documents. A person is visible in the background, looking at the display.

Platform

Outline Dimensions
unit:mm



Note:1.OSD membrane can be on front or rear cover.
2.4 different AD boards can be selectable.
3.Light sensor and VR are optional function.
4.Temper glass and touch screen can be installed.

██████████