

Platform Specifications



Platform

Key Features

- Sunlight Readable
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Fast Response Time
- Thin and Light



SLO4212 (AUO T420XW01)	
Model No.	SLO4212
LCD Display	42" WXGA TFT LCD Module
Display Area	930.25x523.01mm
Brightness	500 cd/m ²
Resolution	1366x768 (WXGA)
Contrast Ratio	1200 : 1
Pixel Pitch (mm)	0.51075(H) x 0.51075(V)
Viewing Angle	+85°~-85°(H), +85°~-85°(V)
Display Colors	16.7M colors
Response Time	8ms (Typical)
Sync	LVDSx2
Power Consumption	300W
Inverter	DPS-290BP
Control Board (Optional)	AD5621GA (Standard)
F / R Control Button	Power Switch, Menu, Select (+,-), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock....
Dimensions (WxHxD)	1028x621x107mm
Weight	41.5kgs
Optional	☒ Touch Screen

Specifications are subject to change without notice. All brands or product names are trademarks or registered trademarks of their respective companies.

Control Board (Optional)	AD5621GA/AD5621GD/AD5766GDVA/AD1501GDV
☒ AD5621GA	VGA+Audio
☒ AD5621GD	VGA+DVI
☒ AD5766GDVA	VGA+CVBS+S-Video+Audio (Optional DVI / Component)
☒ AD1501GDV	VGA+DVI+S-Video
F / R Control Button	5 Key / 4 Key (Optional)
☒ 5 Key	Power Switch, Menu, Select (+,-), Auto
☒ 4 Key	Power Switch, Menu, Select (+,-)

SLO= Open Frame

SLD= Industrial Casing

